

LNRT-2B-1200

Undercounter, Refrigerator, Two-section, 11 cu. ft., Stainless steel inside and outside, 5" leg, Adjustable shelves, Digital temperature control system, Side mount compressor, 1/4 HP (115V 60Hz), 1/5 HP (220~240V 50Hz), 1/3 HP (220~240V 60Hz), Auto defrosting system



Technical Features

- Removable evaporator
- Detachable side cover
- Back breathing
- Energy-saving hot pipe
- High density polyurethane insulation

Specification

Capacity	300L / 11cu. ft.
Exterior Dimension (W x D x H)	1200 x 700 x 850(mm) 47.2 x 27.6 x 33.5(inch)
Packing Dimension (W x D x H)	1220 x 717 x 905(mm) 48 x 28.2 x 35.6(inch)
Net Weight	82kg / 182lb
Packing Weight	101kg / 224lb
No. of Legs	4
No. of Shelves	2
Door	2 Swing Doors
Compressor (hp, 115V 60Hz)	1/4
Compressor (hp, 220~240V 50Hz)	1/5
Compressor (hp, 220~240V 60Hz)	1/3
Refrigerant (115V 60Hz)	R-134a
Refrigerant (220~240V 50Hz)	R-134a
Refrigerant (220~240V 60Hz)	R-134a
Range of Temperature	0~7 °C / 28~39 °F
Voltage / Frequency	115 V / 60 Hz 220~240 V / 50 & 60 Hz
Rated Input (A/W, 115V 60Hz)	3.0 A / 250 W
Rated Input (A/W, 220~240V 50Hz)	1.1 A / 200 W
Rated Input (A/W, 220~240V 60Hz)	1.1 A / 200 W
Defrosting	Auto
Certification	CE