



LRT-771H

Reach-in, Refrigerator, 19 cu. ft., Stainless steel inside and outside, 4" caster, Adjustable shelves, Digital temperature control system, Top mount compressor, 1/3 HP, 115 V / 60 Hz, 220~240 V / 50 & 60 Hz, Auto defrosting system

Technical Features

- Evaporation tray
- Drain hole inside the cabinet
- Digital temperature control system
- Efficient refrigeration system
- High-density polyurethane insulation

Specification

Capacity	581L / 19cu.ft
Exterior Dimension (W x D x H)	681 x 787 x 2092(mm) 26.8 x 31 x 82.4(inch)
Packing Dimension (W x D x H)	720 x 825 x 2104(mm) 28.3 x 32.5 x 82.8(inch)
Net Weight	106kg / 236lb
Packing Weight	120kg / 267lb
No. of Casters	4
No. of Shelves	4
Door	2 Swing Doors
Compressor (hp)	1/3
Refrigerant	R-134a
Range of Temperature	0~7 °C / 28~39 °F
Voltage / Frequency	115 V / 60 Hz 220~240 V / 50 & 60 Hz
Rated Input (A/W, 115V 60Hz)	6.4 A / 600 W
Rated Input (A/W, 220~240V 50Hz)	2.0 A / 350 W
Rated Input (A/W, 220~240V 60Hz)	2.0 A / 350 W
Defrosting	Auto
Certification	Safety - ETL Sanitation - ETL CE