



## LFT-1471H

Vertical freezer,  $1175 \,\ell$ , stainless steel interior/exterior, 4-inch casters, adjustable shelf height, digital temperature control, upper machine room type, compressor 3/4 horsepower,  $115 \,V/60 \,Hz$ ,  $220-240 \,V/50 \,\&\,60 \,Hz$ , automatic defrost removal

## **Product Features**

- Both the interior and exterior are made of stainless steel, so it can be used without fear of rust, stains, or corrosion.
- The indirect cooling method automatically removes frost, allowing hygienic use without bacteria.
- Even if the refrigerator door is opened frequently, less cold escapes, so the internal temperature is maintained uniformly, and it is a cooling method that quickly returns to the set temperature.
- Using a urethane foam door effectively blocks external heat and keeps food fresh by preventing internal cold air from leaking out.
- There is a shelf hanger on the inside side, so you can adjust the shelf height as desired.

## Specification

Volume	1175L/42cu.ft	
PRODUCT SIZE	1370 x 787 x 2092(mm)	
$(W \times D \times H)$	54 x 31 x 82.4(inch)	
SIZE after packaging	1410 x 825 x 2104(mm)	
(W x D x H)	55.5 x 32.5 x 82.8(inch)	
product weight	173kg/384lb	
Weight after packaging	190kg/422lb	
Caster quantity	4	
shelf quantity	8	
door	4 Swing Doors	
Compressor (hp)	3/4	
Refrigerant	R-404A	
temperature range	-24~-3 °C / -9~5°F	
rated voltage	115 V / 60 Hz	
	220~240 V / 50 & 60 Hz	
Date diamet		
Rated input (A/W, 115V 60Hz)	11.3 A/1050 W	
, , , , , , , , , , , , , , , , , , , ,		
Rated input	5.5 A/930 W	
(A/W, 220~240V 50Hz)	2.5 A/ 25U W	
Rated input		
(A/W, 220~240V 60Hz)	5.5 A/930 W	
defrost	Auto	
	Safety - ETL	
certification	Sanitation - ETL	
	CE	